



| Pos | Qty | Part No. | Description | Ordernumber |
|-----|-----|--------------|----------------------------------|-------------------------------------|
| 1 | 1 | 900025 | Muffler BOS Oval120 Carbon Steel | BM12R02-OVCS - Carbon Steel |
| | | 80005 | Mounting Parts: | Weight: |
| 2 | 1 | 72183 | Link Pipe | Stock: 6,2 kg |
| 3 | 1 | 64500 | Mounting Bracket | Bos: 3,4 kg |
| 4 | 2 | 14140 | Bolt M6x16 | |
| 5 | 1 | 14087 | Pull Spring 48 mm. | Noiselevel: @ 3750 rpm |
| 6 | 1 | 64538 | Standstop | Stock: Specified 90,0 dB(A) |
| 7 | 1 | 14058 | Spring Washer M8 | Measured 85,6 dB(A) |
| 8 | 2 | 14063 | Bolt M8x12 ISO7380 | Bos: With DBeater 88,0 dB(A) |
| 9 | 1 | 64560 | Clamp 55-59 | Open 90,7 dB(A) |

Performance

Stock: 99,6 Hp / 7570 rpm

Bos: 101,3 Hp / 7378 rpm

Max. Hp incr.: + 2,4 Hp / 7375 rpm

Max Nm incr.: + 2,3 Nm / 5130 rpm

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.

After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.